

PipeFit Clamps

Dinex has developed a new clamp range from our clamp factory in England suitable for heavy duty pipes.

- Designed to connect exhaust pipes (with slotted ends).
- High strength clamps rated to 60Nm installation torque.
- Wide straps cover the whole of the slots on the outer pipe.
- Available for pipe sizes from Ø48mm upwards.
- No loose parts.

Design Features

High strength mechanism designed to compress the outer slotted pipe onto the standard inner pipe OD.

Cylindrical trunnions allow the screws to self-centre to optimise performance.

Socket cap screws provide a strong (12.9 grade) yet compact fastener mechanism.

All fasteners are coated to provide high (>700hours) salt spray resistance**.

35mm wide straps are edge dressed – no sharp burrs – and made from 409 stainless steel for longer life.

** in accordance with BS 7479 (ASTM B117) ISO 3768.



Dinex no.	Inner Pipe Size		Clamp Size Range [mm]
	mm	Inch	
99815	47.6	1 7/8	Ø48 - Ø54
99800	50.8	2	Ø51 - Ø57
99801	57	2 1/4	Ø57 - Ø63
99816	60.3	2 3/8	Ø60 - Ø66
99802	63.5	2 1/2	Ø64 - Ø70
99817	66.7	2 5/8	Ø67 - Ø73
99803	69.9	2 3/4	Ø70 - Ø76
99804	76.2	3	Ø76 - Ø82
99818	79.4	3 1/8	Ø80 - Ø86
99805	85		Ø85 - Ø91
99806	88.9	3 1/2	Ø89 - Ø95
99819	100		Ø100 - Ø106
99807	101.6	4	Ø102 - Ø108
99808	110		Ø 110 - Ø116
99809	114.3	4 1/2	Ø114 - Ø120
99810	120		Ø120 - Ø126
99811	127	5	Ø127 - Ø133
99812	139.7	5 1/2	Ø140 - Ø146
99813	152.4	6	Ø152 - Ø158

