

ButtFit Flat Clamps



- Designed to connect exhaust pipes end to end.
- Strong, reliable yet lightweight and flexible.
- No need to separate pipes before clamping.
- Simply torque the socket cap screws for fast assembly.*
- Available for pipe sizes from Ø50mm to Ø152.4mm.
- Made from stainless or aluminized steel.

Design Features

75mm wide strap accommodates pipes for fast, easy and accurate installation. Bridging piece helps provide a 360°

seal around the joined pipes and accommodates pipe tolerance variations. Mechanical joints replace spot welds to insure against fatigue failures. Cylindrical trunnions allow the screws to self-centre to optimise performance, but also reinforce the joint.

Socket cap screws provide a strong (12.9 grade) yet compact fastener mechanism.

All fasteners are high strength and coated to provide high corrosion resistance (>700 hours salt spray resistance**).

* Maximum recommended torque = 25Nm.

** In accordance with BS 7479 (ASTM B117) ISO 3768.



Dinex no.

Aluminized	Inox	B mm	B Inch
99350/T	99450/T	50.8	2
99357/T	99457/T	57.0	2 1/4
99360		60.3	2 3/8
99363/T	99463/T	63.5	2 1/2
99370/T	99470/T	69.9	2 3/4
99376/T	99476/T	76.2	3
99389/T	99489/T	88.9	3 1/2
99402/T	99502/T	101.6	4
99408		108	4 1/2
99414/T	99514/T	114.3	4 1/2
99427/T	99527/T	127.0	5
99428		140	5 1/2
99455/T	99553/T	152.0	6

